

TECHNICAL SPECIFICATION



Jetstream® Constructor Kits

Jetstream®TH2P R SL Constructor Kit / CBP020-000-000



DESCRIPTION

Jetstream® is a belt-mounted rechargeable respirator with a large capacity disposable filter supplying filtered air through a highly flexible reinforced hose to a variety of head tops for different applications.

The Jetstream® Constructor kit carry case contains:

EVO®5 safety helmet complete with sealed polycarbonate visor

Flexible hose

TH2P R SL dust or TH2A2P R SL gas and dust filters

Flow meter

Rechargeable battery

Multi-region plug adaptor

OPTIONS

Jetstream®TH2P R SL Constructor Kit (CBP020-000-000)

Jetstream® TH2A2P R SL Constructor Kit
(CDP020-000-000)

SAFETY STANDARDS

EN 397 • EN 166 • EN 12941



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
























Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 20 Feb 2023 / Copyright 2018 - 2023. JSP Limited. All Rights Reserved.



SPECIFICATIONS

	Impact Resistance 50 Joules		Molten Metal Yes - Helmet Only
	Maximum Temperature +50°C		Minimum Temperature -20°C
	HDPE Shell Yes		Recyclable Shell
	Textile Harness		Slip Ratchet Slip
	Ventilation No		Integrated Eyewear Fitted
	Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional		Manufacturer's Trademark JSP Dagger
	Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use) 1		Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles. B
	Protection from Liquid Droplets 3		Resistance to Molten Metals and Hot Solids (optional) 9
	BSI Kitemark Yes		JSPCheck Yes
	Classification TH2 (Turbo Hood)		Usage R (Reusable)
	Minimum Filtration Efficiency 98%		Maximum Total Inward Leakage (TIL) 2% When Fitted To Jetstream
	Nominal Protection Factor 50		UK Assigned Protection Factor 20
	Face Seal Type Hypoallergenic Material		Exhalation Valve Yes
	Mask Design A Turbo Hood Powered Air Purifying Respirator (Loose Fitting)		Latex free No
	Metal Free No		Battery Type 8 Hour Rechargeable Nickel Metal Hydride (NiMH)
	Product Weight Head Top 884g		Noise Level 65dB
	Filter Type P (Protects Against Solid and Liquid Aerosols)		*** Gas Filters Not Compatible ***
	Product Weight Power Pack & Filter 1066g		Product Weight TH2P R SL Filter 124g

FEATURES



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 20 Feb 2023 / Copyright 2018 - 2023. JSP Limited. All Rights Reserved.





Comfort

Waist mounted blower unit with fully automatic alarm and integrated battery attached to a wide comfortable waist belt.



Adaptable

A wide range of kits, filters and head tops are available to suit a variety of tasks.



High Performance Filters

TH2P R SL (A Reusable Solid & Liquid, Particulate Aerosol Filter)

RANGE

DOWNLOADS



[Image Pack \(ZIP\)](#)

[doc-jetstream-constructor-kit.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 20 Feb 2023 / Copyright 2018 - 2023. JSP Limited. All Rights Reserved.

