



PRODUCT INFORMATION

| | |
|--------------------------------|-----------|
| Item Number | RE0360 |
| Size Range | 8-11 |
| Primary Coating Polymer | Latex |
| Max Working AC Voltage | 1000.00 V |

FEATURES

Electrical Handling: Class 0, for a maximum working AC voltage of 1000V

Flexibility: Industry leading latex manufacturing techniques and expertise allows gloves to be as soft and thin as possible offering the maximum level of the dexterity to the user

Length: 36cm length for protection up the wrist

Chemical Resistant: Passes special properties 'AZC' for protection against acid, ozone and extremely low temps

Electrical Handling: Designed to be used in conjunction with our leather Protector Gauntlet (RE-PRO & RE-PRO/NB) for additional longevity and mechanical protection
Excellent electrical resistance

Lining: Lightly powdered to ensure easy donning and doffing

SECTORS

Automotive • Construction & Utility

STANDARDS



PPE CAT III



0333



CAUTION

Contains latex which may cause allergic reactions, including anaphylactic response.
Contains accelerator chemicals which may cause type IV skin irritation and contact dermatitis in sensitised individuals.

STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. You are advised to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear.

DISPOSAL INSTRUCTIONS

Dispose of responsibly and in line with local guidance.

PACKING

1 pair per bag
1200 pairs per pallet

Reusable Gloves

Electrical Handling

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555

| Size | Outer Packaging Barcode |
|------|-------------------------|
| 8 | 05010699855404 |
| 9 | 05010699855398 |
| 10 | 05010699855411 |
| 11 | 05010699855435 |
| | |
| | |

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555